



PRODUCT SPECIFICATIONS

Model Number	2.4L
Cylinders	4
Combustion System	Spark-ignited
Cooling System	Water-cooled
Displacement	143 cid (2.351 L)
Compression Ratio	9:5:1
Bore & Stroke	3.40 in x 3.93 in (86.5 mm x 100 mm)
Fuel Type	GASOLINE, NATURAL GAS (NG), PROPANE (LP)
Direction of rotation	Counter-clockwise viewed on flywheel

SAE J1995 rated following 36300018 PSI Derate Specification with a tolerance of +/-5%. Power and torque values are based on standard assumptions. kW values are based on standard assumptions for mechanical and electrical losses. Ratings and performance are solely for reference only and subject to site conditions and PSI application and ratings guidelines. The product images shown are for illustration purposes only and may not be an exact representation of the final product. All information is subject to change without notice.

[REQUEST INFO](#)



POWER RATINGS

GENERAL DATA & FEATURES

DIMENSIONS

- Fuel options: LPG, CNG, gasoline
- Sequential Electronic Fuel Injection (SEFI) for gasoline
- Fuel and emission control system that meets Tier II EPA/CARB emission regulations for LSI engines
- SAE flywheel housings and flywheels
- Additional crankshaft pulleys
- Cooling fans
- Radiator
- Electronic governors
- Remote oil filter and auxiliary oil drain
- Metal engine skid

- Premium timing and balance belts
- High silicon content pistons for improved durability and noise reduction
- Sintered powdered-metal exhaust valve seat inserts for enhanced durability
- World-class engine sealing system for superior leak protection
- Integral harmonic balancer/crankshaft pulley for easier accessory drive dress
- Intake/exhaust manifolds standard
- Emission Certified with U.S. EPA and CARB – Industrial Mobile