

FLIFT

AMERICA

XCR40

EXCAVATOR

Well Equipped @ \$49570

Overview

Operating Weight 8818 (lbs)
Bucket Capacity: 0.12cbm, 0.18cbm, 0.36cbm
Enclosed Operator Cabin -- A/C & Heat

Features

Hyd. Quick Attach
Dozer Blade
Joystick
Swing Boom
Thumb
Rubber Tracks

Engine

Kubota D1703 In-line 4 Cyl
30HP @ 2800RPM
Engine Oil Capacity 7 (l)

Performance Specs

Traveling Speed (high/low) 2.75mph/1.5mph
Gradeability 58%
Max. Bucket Digging Force 6834 (lbf)
Arm Digging Force 4091 (lbf)
Ground Pressure 4.641 (psi)
System Pressure 3263 (psi)
Flow Rate 23.25 (gpm)
Machine Weight 8818 (lbs)
Boom Length 99.8 (in)
Arm Length 55.12 (in)
Fuel Tank Capacity 11 (gal)
Hydraulic Tank Capacity 12.81 (gal)
Carrier Roller (each side) 1
Supporting Roller (each side) 4

Dimensions

Overall Length 193.5 (in)
Overall Width 67.7 (in)
Overall Height 99.4 (in)
Ground Clearance 11.6 (in)
Track Width 11.8 (in)
Axle Base (Track length on ground) 65.7 (in)
Length of track 84.8 (in)

Operation Parameters

Max. Digging Radius 215.7 (in)
Max. Digging Depth 126.3 (in)
Max. Digging Height 189 (in)
Max. Dumping Height 134.1 (in)
Max. Vertical Digging Depth 126.3 (in)

