

FLIFT
AMERICA

GAMBIT
ELECTRIC

Well Equipped @ \$26947



www.FLIFTAmerica.com



DEALER CONTACT

Model			3300E	4400E	5500E	6600E	7700E	
General	Power Type		Electric	Electric	Electric	Electric	Electric	
	Rated Capacity	lbs	3300	4400	5500	6600	7700	
	Load Center	in	20	20	20	20	20	
	Lift Height (M300)	in	118	118	118	118	118	
Characteristic & Dimension	Fork Size	L x W x T	in 36x4.75x1.4	42x4.75x1.5	42x4.75x1.5	42x5x1.75	42x5x1.75	
	Mast Tilt Angle	F/R	Deg 6°/12°	6°/12°	6°/12°	6°/12°	6°/12°	
	Front Overhang (Wheel Center to fork face)	in	17	18	18	19	19	
	Tread	F/R	in 35/36	38/37	38/37	39/38	39/38	
	Ground Clearance (Bottom of mast)	in	4.5	4.5	4.5	5	5	
	Overall Dimension	Length to face of fork (Without fork)	in	85	93	93	101	101
		Overall Width	in	43	45	45	48	48
		Mast Lowered Height	in	79	82	82	83	83
		Mast Extended Height (With backrest)	in	155	158	158	164	164
	Overall Guard Height	in	85	88	88	86	86	
	Turning Radius (Outside)	in	77	82	82	91	91	
	Min. Insecting aisle	in	81	89	89	95	95	
Performance	Speed	Travel (Empty load)	mph	10	10	10	10	
		Lifting (Full load)	in/s	11	12	12	12	
	Max. Gradeability	%	15	15	15	15	15	
Chassis	Tire	Front		6.50-10-10PR	7.00-12-12PR	7.00-12-12PR	28*9-15-12PR	28*9-15-12PR
		Rear		5.00-8-10PR	18*7-8-14PR	18*7-8-14PR	18*7-8-14PR	18*7-8
	Wheel Base	in	54	59	59	67	67	
Service Weight	lbs	6768	9193	9722	11243	11684		
Power & Transmission	Motor	Drive Motor	in	10.7	14.75	14.75	20	20
		Lift Motor	in	11.5	11.5	11.5	16	16
	Battery	Voltage/Capacity	V/Ah	48/440	48/560	48/630	80/500	80/550
	Controller	Manufacturer		INMOTION	INMOTION	INMOTION	INMOTION	INMOTION
Type			AC	AC	AC	AC	AC	
Operating Pressure for Attachment	Mpa	14.5	17.5	17.5	17.5	17.5		



WHY FLIFT?
 200+ ELECTRIC MODEL CONFIGURATIONS
 UP TO 4HR WORKING TIME
 ZERO EMISSIONS
 STANDARD SIDE SHIFT
 SELECTABLE CAPACITY
 SELECTABLE COLOR(S)
 SELECTABLE MAST
 SELECTABLE FORK SIZE
 SELECTABLE PNEUMATIC OR SOLID TIRES
 OPTIONAL DUAL WHEEL
 OPTIONAL FORK POSITIONER
 INDUSTRY BEST (STD) WARRANTY

