



Clear Leader in Value, Endless Versatility, & Multiple Models to Choose From!

Product Parameters:

MODEL	LTX25	LTX35	LTX65	LTX75	LTX100	LTX125
Operating Capacity (lb)	838	1543	2200	2300	2645	3300
Max Speed (mph)	6	7	8/11	8/11	8/11	8/11
Auxiliary Flow (gpm)	13.2	15	21	21	23	23
Tire (Track) Model	200x72	300x52.5	320x84	320x84	320x84	450x86
Engine	Cummins QSF2.8	Cummins QSF2.8	Cummins QSF2.8	Cummins QSF2.8	Cummins QSF3.8	Cummins QSF3.8
Power	75HP	75HP	75HP	75HP	100HP	100HP
Rated Power (hp)	75	75	75	75	100	100
Fuel Tank Capacity (gal)	7.4	13.2	23.7	23.7	23.7	23.7
Operating Weight (lb)	3086	6613	9259	9259	10582	10582
Self Weight Bucket (lb)	3086	6172	8377	8377	9920	10582
Bucket Capacity (ft ³)	7.1	10.6	17.7	17.7	19.5	21.2

Dimensions:

MODEL	LTX25	LTX35	LTX65	LTX75	LTX100	LTX125
Overall Operating Height (In)	134	132	137	137	189	160
Height to Top of Cab (In)	71	81	85	85	85	85
Length w/o Bucket (In)	87	90	108	108	118	118
Length w/ Bucket (In)	118	116	138	138	146	146
Dumping Height (In)	79	83	88	88	97	97
Width (In)	36	55	70	70	79	84
Bucket Width (In)	42	59	72	72	80	80
Height to Bottom of Bucket (In)	96	103	108	108	117	117
Dumping Angle @ Max Height (°)	40	40	40	40	40	40
Height to Bucket Hinge Pin (In)	98	109	114	114	124	124
Dumping Reach (In)	18	32	28	28	28	28
Rollback of Bucket on Ground (°)	30	30	30	30	30	30
Rollback of Bucket at Full Height (°)	103	104	104	104	104	104
Wheelbase (In)	32	49	59	59	59	59
Ground Clearance (In)	6	6	8	8	8	8
Angle of Departure (°)	20	20	20	20	20	20
Front Turning Radius w/o Bucket (In)	38	42	51	51	54	54
Front Turning Radius w/ Bucket (In)	65	72	79	79	87	87
Rear Turning Radius (In)	49	50	67	67	69	69
Rear Axle to Bumper (In)	29	24	35	35	37	37
Tread Width (In)	29	43	58	58	65	65

