

Well Equipped starting @ \$34778



www.FLIFTAmerica.com

"S" STANDS FOR SUPERIOR

ALL Gambit-S models are crafted with our exclusive perimeter frame, floating cab design, allowing the cockpit and ROPS to move independently from the chassis. Thus, reducing vibration as much as 15% when compared to our competitors.


General	Model				4400P	5500P	6600P	7700P
	Power Type		1000	LPG	LPG	LPG	LPG	
	Rated Capacity		lbs	4400	5500	6600	7700	
	Load Center		in	20	20	20	20	
Dimensions	Lift Height (S450)		in	177	177	177	177	
	Fork Size		LxWxT	in	60x5x1.5	60x5x1.5	60x5x1.75	60x5x1.75
	Mast Tilt Angle		F/R	Deg	6/12	6/12	6/12	6/12
	Front Overhang (Wheel Center to fork face)		in	18	18	19	19	
	Ground Clearance (Bottom of mast)		in	4	4	5.5	5.5	
		Length to face of fork(Without fork)		in	102	102	107	109
		Overall Width		in	45	45	48	48
	Overall	Mast Lowered Height		in	81	81	85	85
ð	Dimension	Free lift distance		in	4	4	5	5
		Mast Extended Height(With backrest)		in	219	219	223	223
		Overhead Guard Height		in	84	84	85	85
	Turning Radius(outside)			in	90	90	95	97
	Min. intersecting aisle			in	94	94	98	100
	Min. right angle stacking aisle width		in	157	157	162	164	
8	Speed	Max. Travel Speed		mph	12	12	13	13
Performance		Lifting Speed (full load/no load)		in/s	21/23	21/23	20/22	17/19
		Lowering Speed (Full load/no load)		in/s	≤24/≥12	≤24/≥12	≤24/≥12	≤24/≥12
	Max. Gradeability		%	20	20	20	20	
Chassis	Tire		1. N	7.00-12-12PR	7.00-12-12PR	28*9-15-14PR	28*9-15-14PF	
	ine	Rear			6.50-9-10PR	6.50-9-10PR	6.50-10-10PR	6.50-10-10PF
	Wheel Base		in	63	63	67	67	
	Service Weight			lbs	8135	8575	9700	10141
	Battery	Voltage/Capacity		V/Ah	12/80	12/80	12/80	12/80
Power & Transmission		Model			2.4	2.4	2.4	2.4
	Engine	Manufacturer			PSI	PSI	PSI	PSI
		Rated output/r.p.m.		hp	63/2700	63/2700	63/2700	63/2700
		Rated torque/r.p.m.		ft-lbs	124/2400	124/2400	124/2400	124/2400
		No. of Cylinder			4	4	4	4
		BorexStroke		mm	86.5x100	86.5x100	86.5x100	86.5x100
		Displacemaent		L	2.4	2.4	2.4	2.4
		Fuel Tank Capacity		gal	16	16	16	16
	Transmission	Туре			Hydraulic	Hydraulic	Hydraulic	Hydraulic
	ransmission	stage FWD/RVS		1.1.1.1	1/1	1/1	1/1	1/1
	Ope	rating Pressure for	Attachment	Mpa	18	18	18	18

WHY FLIFT?

100+ LPG MODEL CONFIGURATIONS STANDARD SIDE SHIFT PSI 2.4L LP ENGINE SELECTABLE CAPACITY SELECTABLE COLOR(S) SELECTABLE MAST SELECTABLE FORK SIZE SELECTABLE PNEUMATIC OR SOLID TIRES OPTIONAL CAB W/ HEAT & AIR OPTIONAL CAB W/ HEAT & AIR OPTIONAL FORK POSITIONER INDUSTRY BEST (STD) WARRANTY



DEALER CONTACT





www.FLIFTAmerica.com

800.395.1162 info@fliftamerica.com

