

FLIFT

AMERICA

GAMBIT

6600/7700 DIESEL

Well Equipped @ \$32280





Model		GAMBIT 6600	GAMBIT 7700	
General	Power Type	Diesel	Diesel	
	Rated Capacity	lbs 6600	7700	
	Load Center	in 20	20	
Dimensions	Min. Lift Height (M300)	in 118	118	
	Fork Size	LxWxT in 42x5x1.75	42x5x2	
	Mast Tilt Angle (F/R)	Deg 6°/12°	6°/12°	
	Front Overhang (Wheel Center to fork face)	in 19	20	
	Ground Clearance (Bottom of mast)	in 5	4	
	Overall Dimension	Length to face of fork (Without fork)	in 107	113
		Overall Width	in 48	48
		Mast Lowered Height (M300)	in 83	85
		Mast Extended Height (With backrest)	in 164	164
	Overall Guard Height	in 82	82	
Turning Radius (outside)	in 96	102		
Min. insecting aisle	in 98	104		
Performance	Speed	Travel (Empty load)	mph 12	12
		Lifting (Full load)	in/s 21	14
	Max. Gradeability	% 20	20	
Chassis	Tire	Front	28x9-15-12PR	28x9-15-12PR
		Rear	6.50-10-10PR	6.50-10-10PR
	Wheel Base	in 70	71	
Service Weight	lbs 9460	9900		
Power & Transmission	Battery	Voltage/Capacity	V/Ah (12V/80Ah)	(12V/80Ah)
	Engine	Model	D04EG-NA	D04EG-NA
		Manufacture	Mitsubishi	Mitsubishi
		Rated output/r.p.m.	hp 48/2250	48/2250
		Rated torque/r.p.m.	ft lbs 130/1800	130/1800
		No. of Cylinder	4	4
		BorexStroke	mm 94*120	94*120
		Displacemaent	L 3.3	3.3
	Fuel Tank Capacity	gal 16	16	
	Transmission	Type	Hydraulic	Hydraulic
Stage		FWD/RVS	1/1	1/1
Operating Pressure for Attachment	Mpa 17.5	17.5		

DEALER CONTACT



WHY FLIFT?

- 200+ DIESEL MODEL CONFIGURATIONS
- STANDARD SIDE SHIFT
- SELECTABLE MITSUBISHI OR DOOSAN ENGINE
- SELECTABLE CAPACITY
- SELECTABLE COLOR(S)
- SELECTABLE MAST
- SELECTABLE FORK SIZE
- SELECTABLE PNEUMATIC OR SOLID TIRES
- OPTIONAL CAB W/ HEAT & AIR
- OPTIONAL DUAL WHEEL
- OPTIONAL FORK POSITIONER
- INDUSTRY BEST (STD) WARRANTY