## 

AMERICA

## **GAMBITS**

DIESEL

Well Equipped @ \$33181





www.FLIFTAmerica.com



DEALER CONTACT



ALL Gambit-S models are crafted with our exclusive perimeter frame, floating cab design, allowing the cockpit and ROPS to move independently from the chassis. Thus, reducing vibration as much as 15% when compared to our competitors.

_	Model				GAMBIT-S 6600	GAMBIT-S 6600	GAMBIT-S 7700	GAMBIT-S 770
General	Power Type				Diesel	Diesel	Diesel	Diesel
gen	Rated Capacity			lbs	6600	6600	7700	7700
O	Load Center			in	20	20	20	20
	Min. Lift Height (M300)			in	118	118	118	118
suo	Fork Size LxWxT		in	42x5x1.75	42x5x1.75	42x5x2	42x5x2	
	Mast Tilt Angle	F/R		Deg	6/12	6/12	6/12	6/12
	Front Overhang (Wheel Center to fork face)			in	19	19	19	19
	Ground Clearance (Bottom of mast)			in	5.5	5.5	5.5	5.5
JS I		Length to face of fork (Without fork)		in	108	108	109	109
Dimensions			Overall Width	in	48	48	48	48
	Overall Dimension	Mast Lowered Height (M300)		in	83	83	85	85
		Mast Extended Height (With backrest)		in	163	163	163	163
		Ov	erhead Guard Height	in	85	85	85	85
	Turning Radius (outside)			in	95	95	97	97
	Min. intersecting aisle		in	98	98	100	100	
Performance	Speed	1	Fravel (Empty load)	mph	13	13	13	13
Ē		Lifting (Full load)		in/s	20	20	17	17
Per		Max. Grad	eability	%	20	20	20	20
un.	Tire	Front			28*9-15-14PR	28*9-15-14PR	28*9-15-14PR	28*9-15-14PR
Chassis	1116	Rear			6.50-10-10PR	6.50-10-10PR	6.50-10-10PR	6.50-10-10PR
2		Wheel 8	3ase	in	67	67	67	67
0	Service Weight		lbs	9370	9370	9810	9810	
Power & Transimission	Battery		Voltage/Capacity	V/Ah	12/80	12/80	12/80	12/80
		Model			DM02-LEF02	D04EG-NA	DM02-LEF02	D04EG-NA
		Manufacture			Doosan D24	Mitsubishi	Doosan D24	Mitsubishi
	Engine	Rated output/r.p.m.		hp	75/2600	48/2250	75/2600	48/2250
		Rated torque/r.p.m.		ft lbs	236/1600	130/1800	236/1600	130/1800
		No. of Cylinder			4	4	4	4
		Bore*Stroke		mm	90*94	94*120	90*94	94*120
5		Displacemaent		L	2.4	3.3	2.4	3.3
5		Fuel Tank Capacity		gal	16	16	16	16
Pow		Туре			Hydraulic	Hydraulic	Hydraulic	Hydraulic
	Transmission	stage	FWD/RVS		1/1	1/1	1/1	1/1
	Operating Pressure for Attachment		Mpa	18	18	18	18	

## CONTROL CHARA PER



## **WHY FLIFT?**

50+ DIESEL MODEL CONFIGURATIONS
STANDARD SIDE SHIFT

SELECTABLE MITSUBISHI OR DOOSAN ENGINE
SELECTABLE CAPACITY
SELECTABLE COLOR(S)
SELECTABLE MAST
SELECTABLE FORK SIZE
SELECTABLE PNEUMATIC OR SOLID TIRES
OPTIONAL CAB W/ HEAT & AIR
OPTIONAL DUAL WHEEL
OPTIONAL FORK POSITIONER
INDUSTRY BEST (STD) WARRANTY



