



DEALER CONTACT

General	Model			TLR 6600
	Power Type			Diesel
	Rated Capacity		Ibs	6600
	Lift Capacity @ Max Extended		lbs	5060
Characreristic & Dimension	Lift Height		ft	22.5
	Fork Size	L×W×T	in	48x5x2
	Carriage Dump/Rollback		Deg	43°/38°
	Forward Reach (1 ton)		in	142
	Ground Clearance		in	14
	Overall Dimension	Overall Length to Front of Carriage	in	183
		Overall Width	in	85
		Overall Height	in	91
		Width of Cab	in	32
		Wheelbase	in	112
Performance	Front Track Width		in	69
	Turning Radius (outside)		in	167
	Speed	Travel (Empty load)	mph	15
		Boom Raise	sec	10
		Boom Extend	sec	12
Chassis	Tire	Front		16/70-20
		Rear		16/70-20
	Steering		4-Wheel	
	Service Weight		lbs	15950
Power & Transmission	Battery	Voltage/Capacity	V/Ah	(12V/120Ah
	Engine	Model		QSF2.8 T4F
		Manufacture		Cummins
		Rated output/r.p.m.	hp/rpm	66/2500
		Rated torque/r.p.m.	ft lbs	170/1600
		No. of Cylinder		4
		Bore×Stroke	mm	94*100
		Displacement	L	2.8
		Fuel Tank Capacity	gal	25
	Transmission	Туре		Hydraulic
		Stage FWD/RVS		2/2
	Operating Pressure for Attachment		Мра	21
	1	gal	18.5	

WHY FLIFT? 20+ ATTACHMENTS STANDARD ENCLOSED CAB W/ HEAT & AIR CUMMINS POWERED SELF LEVELING FORKS 4-WHEEL DRIVE W/ TORQUE PROPORTIONING 3 STEERING MODE 4-WHEEL STEERING LINE RUPTURE PROTECTION VALVE PNEUMATIC AGRICULTURAL TIRES POWERSHIFT 2 SPEED GEARBOX AIR BRAKES UHMWPE BOOM WEARING PADS INDUSTRY BEST (STD) WARRANTY





www.FLIFTAmerica.com

