

FLIFT
AMERICA

4400R
LITHIUM ION

Well Equipped @ \$39999



www.FLIFTAmerica.com



DEALER CONTACT

		4400R-75Li	4400R-60Li	4400R-50Li
Power Type		Lithium	Lithium	Lithium
Driving Style		Standing	Standing	Standing
Rated Load Capacity	lb	4400	4400	4400
Load Center	in	20	20	20
Wheelbase	in	65	65	65
Vehicle Weight	lb	9039	8488	8488
Tire Type		PU	PU	PU
Load-bearing Wheel	mm	130*85	130*85	130*85
Drive Wheel	mm	343*135	343*135	343*135
Auxiliary Wheel	mm	180*76	180*76	180*76
Mast Lowered Height	in	131	110	94
Tilt Range ° Fwd/Back		2 / 4	2 / 4	2 / 4
Lifting Height	in	295	236	196
Mast Extended Height	in	334	275	235
Free Lift	in	93	71	50
Truck Length	in	80/110	80/110	80/110
Truck Width	in	59	59	59
Fork Size	in	42 x 4.75 x 1.5	42 x 4.75 x 1.5	42 x 4.75 x 1.5
Fork Spread	in	10-32	10-32	10-32
Reach Stroke	in	24	24	24
Minimum Ground Clearance	in	1.5	1.5	1.5
Turning Radius	in	75	75	75
Driving Speed, full/empty	Km/h	7 / 8	7 / 8	7 / 8
Lifting Speed, full/empty	mm/s	150/260	150/260	150/260
Descending Speed, full/empty	mm/s	300/160	300/160	300/160
Maximum Climbing Ability °, full/empty		5 / 8	5 / 8	5 / 8
Brake Type		Electromagnetic	Electromagnetic	Electromagnetic
Drive Motor Power	KW	4.5	4.5	4.5
Lifting Motor Power	KW	6.3	6.3	6.3
Battery, Voltage/Capacity	V/AH	48 / 400	48 / 400	48 / 400
Steering System		EPS	EPS	EPS

FLIFT reserves the right to change product design and specifications, parameters are subject to change without prior notice



WHY FLIFT?

200+ LITHIUM MODEL CONFIGURATIONS
 EXTENDED RANGE & QUICK RECHARGE TIME
 ZERO EMISSIONS & STABLE IN ALL CONDITIONS
 COMPARTMENT SENSING
 CARRIAGE MOUNT CAMERA SYSTEM
 SELECTABLE COLOR(S)
 SELECTABLE MAST
 SELECTABLE FORK SIZE
 ELECTROMAGNETIC BRAKING
 24" REACH STROKE
 INDUSTRY BEST (STD) WARRANTY