

AMERICA

## CTX30Q-A LITHIUM ION





DEALER CONTACT



	CTX30Q-A		
FEATURE	Power Type		Lithium
	Capacity	lbs	6600
	Load Center	in	24
	Lifting Height	in	8
DIMENSION	Dimension (L/W/H)	in	65x27x51
	Fork Size	in	45x6x2
	Fork Width	in	27
	Min. Ground Clearance	in	3.3
	Turning Radius	in	56
WEIGHT	Weight (w/ battery)	lbs	419
	Battery Weight	lbs	44
WHEEL	WheelType		Solid PU
	Driving Wheel Size	in	7x2
	Loading Wheel Size	in	3x2.75
DRIMNG & CONTROL	Driving Motor	hp (60min)	1
	Lifting Motor	hp (60min)	1
	Cylinder Diameter	in	2
	Battery Dimension	in	6.25x7.5x4
	Battery Voltage/Capacity	V/ah	2x24/20(30/40)
	Controller		DC
	Working Pressure	mpa	14
PERFORMANCE	Lifting Speed (laden/unladen)	mph	2.17/2.5
	Max Climbing Ability	%	15
	Braking		Electromagnetic
OTHER	Driving Type		Electric
	Steering System		Manual
	Noise Level		63
	Waterproof Grade		IPX4

## **WHY FLIFT?**

200+ LITHIUM MODEL CONFIGURATIONS **ZERO EMISSIONS STABLE IN ALL CONDITIONS INTERCHANGEABLE BATTERY CONTINUOUS OPERATION UP TO 6HRS QUICK RECHARGE TIME 3.5HRS** LED BATTERY LIFE INDICATOR SELECTABLE COLOR(S) **ELECTROMAGNETIC BRAKING INDUSTRY BEST (STD) WARRANTY** 





